

X-WADI



Ausführung construction	Standard standard
	Hochtemperatur (HT) high temperature (HT)
Werkstoff material	Edelstahl (1.4435) stainless steel (1.4435)
Dichtring sealing	TPE / NBR O-RING FPM (HT) FPM
Temperatur temperature	-40°C - +100°C -40°C - +200°C (HT)
Schutzart protection	IP68 - 10 bar / IP69K

einteiliger Dichteinsatz, metrisch / one-piece sealing insert, metric

Art. Nr. art. no.	Art. Nr. HT art. no. HT	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
X-WADIM0803	X-WADIM0803HT	M8x1,25	2,5 - 3,5	11	10	14	50
X-WADIM0805	X-WADIM0805HT	M8x1,25	3,5 - 5	11	10	14	50
X-WADIM1004	X-WADIM1004HT	M10x1,25	3 - 4	13	10	15	50
X-WADIM1006	X-WADIM1006HT	M10x1,25	4 - 6	13	10	15	50
X-WADIM1205	X-WADIM1205HT	M12x1,5	3,5 - 5	17	10	17	50
X-WADIM1206	X-WADIM1206HT	M12x1,5	5 - 6,5	17	10	17	50
X-WADIM1208	X-WADIM1208HT	M12x1,5	6,5 - 8	17	10	17	50
X-WADIM1610	X-WADIM1610HT	M16x1,5	8 - 10,5	19	10	20	50
X-WADIM2015	X-WADIM2015HT	M20x1,5	11 - 15	24	10	21	50
X-WADIM2520	X-WADIM2520HT	M25x1,5	16 - 20,5	30	11	25	25
X-WADIM3225	X-WADIM3225HT	M32x1,5	21 - 25,5	36	13	28	25
X-WADIM4033	X-WADIM4033HT	M40x1,5	28,5 - 33	46	13	31	10
X-WADIM5042	X-WADIM5042HT	M50x1,5	37 - 42	55	14	34	10
X-WADIM6352	X-WADIM6352HT	M63x1,5	46 - 52	70	14	37	5

einteiliger Dichteinsatz, PG / one-piece sealing insert, PG

Art. Nr. art. no.	Art. Nr. HT art. no. HT	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
X-WADIP0705	X-WADIP0705HT	PG7	3,5 - 5	17	10	17	50
X-WADIP0706	X-WADIP0706HT	PG7	5 - 6,5	17	10	17	50
X-WADIP0708	X-WADIP0708HT	PG7	6,5 - 8	17	10	17	50
X-WADIP0910	X-WADIP0910HT	PG9	8 - 10,5	19	10	20	50
X-WADIP1112	X-WADIP1112HT	PG11	8,5 - 12	22	10	21	50
X-WADIP1315	X-WADIP1315HT	PG13	11 - 15	24	10	21	50
X-WADIP1615	X-WADIP1615HT	PG16	11 - 15	24	10	21	50
X-WADIP2120	X-WADIP2120HT	PG21	16 - 20,5	30	12	25	50
X-WADIP2927	X-WADIP2927HT	PG29	23 - 27,5	41	12	28	50
X-WADIP3635	X-WADIP3635HT	PG36	30,5 - 35	50	15	32	25
X-WADIP4242	X-WADIP4242HT	PG42	37 - 42	55	15	34	25
X-WADIP4849	X-WADIP4849HT	PG48	43 - 49	65	15	37	10

X-WADI



X-WADI-HT



nicht durchgehend isolierender Einsatz

not persistent length insulated insert

Auf Anfrage
on request



Multi-einsätze
multi-inserts



Langes Gewinde
long thread



Flachkabeleinsätze
flat cable inserts