


Ausführung construction	starres Innengewinde rigid female thread
Werkstoff material	Polyamid 6, UL94 V0 polyamide 6, UL94 V0
Temperatur temperature	-40°C - +105°C
kurzzeitig short term	+150°C
Schutzart protection	IP68 / IP69K
gemäß according to	IEC EN 61386



metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
SF8B07M12	M12	7	9,0	8	15	35	100
SF8B10M16	M16	10	11,6	11	20	39,4	50
SF8B12M16	M16	12	12,5	11	22	43	50
SF8B17M20	M20	17	18,0	11,5	26	44,35	50
SF8B23M25	M25	23	23,0	11,5	30	53,5	30
SF8B23M32	M32	23	26,0	11,5	38	53,5	30
SF8B29M32	M32	29	29,5	11,5	38	55	20
SF8B29M40	M40	29	29,5	11,5	44	55	20
SF8B36M40	M40	36	36,5	11,5	45	63	20
SF8B48M50	M50	48	48,0	15,5	58	73,5	10
SF8B48M63	M63	48	48,5	18,0	70	76,5	10

PG

Art. Nr. art. no.	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
SF8B07P07	PG7	7	7,1	9,0	17	37,5	100
SF8B10P07	PG7	10	7,1	9,0	17	38,9	50
SF8B10P09	PG9	10	10,1	9,0	20	39,4	50
SF8B12P11	PG11	12	11,5	9,6	24	43,2	50
SF8B12P13	PG13,5	12	13,5	9,5	26	43,1	50
SF8B17P13	PG13,5	17	13,5	9,5	26	44,3	50
SF8B17P13	PG16	17	16,2	9,0	27	43,3	50
SF8B23P21	PG21	23	21,0	11,0	34	57,0	30
SF8B23P29	PG29	23	26,0	13,0	42	59,5	30
SF8B29P29	PG29	29	29,2	13,0	42	59,5	20
SF8B36P36	PG36	36	37,8	13,5	55	68,0	20
SF8B48P48	PG48	48	47,0	15,0	70	76,5	10

Gerade Steck-Verschraubung mit Kunststoff-Innengewinde aus hochwertigem, speziell formuliertem Polyamid. Das Material ist selbstverlöschend, cadmium-, phosphor und halogenfrei sowie schlagfest und sehr gut beständig gegen chemische Stoffe. Extrem stoß- und chemikalienbeständig. Geeignet für industrielle und elektro-technische Installations-Anwendungen sowie für erhöhte Anforderungen in schweren Industrie- und Eisenbahnanwendungen.

Straight fitting with plastic female thread are manufactured from high-grade, specially formulated polyamides. These polyamides are self-extinguishing, free of halogen, phosphor and cadmium. Suitable for industrial and electro technical installation-applications as well as for increased requirements in heavy industry and railway applications and is also used in switch cupboard as conduit terminal.

