

MSF



RINA



Ausführung construction	starres Innengewinde rigid female thread	
Werkstoff material	Polyamid 6, UL94 V0 Messing vernickelt polyamide 6, UL 94 V0 nickel-plated brass	
Temperatur temperature	-40°C - +105°C kurzz. / short term +150°C	
Schutzart protection	IP68 / IP69K	
gemäß according to	IEC EN 61386	
Passende Wellrohre suitable corrugated conduits	alle all	

Verschraubung PA6 mit Metall-Innengewinde
fitting PA6 with female metal thread



Gewindeart metrisch

Art. Nr. schwarz art. no. black	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
M8BSF07M12	M12	7	9,0	8	15	35	100
M8BSF10M16	M16	10	11,6	11	20	39,4	50
M8BSF12M16	M16	12	12,5	11	22	43	50
M8BSF17M20	M20	17	18,0	11,5	26	44,35	50
M8BSF23M25	M25	23	23,0	11,5	30	53,5	30
M8BSF23M32	M32	23	26,0	11,5	38	53,5	30
M8BSF29M32	M32	29	29,5	11,5	38	55	20
M8BSF29M40	M40	29	29,5	11,5	44	55	20
M8BSF36M40	M40	36	36,5	11,5	45	63	20
M8BSF48M50	M50	48	48,0	15,5	58	73,5	10
M8BSF48M63	M63	48	48,5	18,0	70	76,5	10

Gewindeart PG

Art. Nr. art. no.	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
M8BSF07P07	PG7	7	7,1	9,0	17	37,5	100
M8BSF10P07	PG7	10	7,1	9,0	17	38,9	50
M8BSF10P09	PG9	10	10,1	9,0	20	39,4	50
M8BSF12P11	PG11	12	11,5	9,6	24	43,2	50
M8BSF12P13	PG13,5	12	13,5	9,5	26	43,1	50
M8BSF17P13	PG13,5	17	13,5	9,5	26	44,3	50
M8BSF17P13	PG16	17	16,2	9,0	27	43,3	50
M8BSF23P21	PG21	23	21,0	11,0	34	57,0	30
M8BSF23P29	PG29	23	26,0	13,0	42	59,5	30
M8BSF29P29	PG29	29	29,2	13,0	42	59,5	20
M8BSF36P36	PG36	36	37,8	13,5	55	68,0	20
M8BSF48P48	PG48	48	47,0	15,0	70	76,5	10

