

|                                   |   |
|-----------------------------------|---|
| <b>Ausführung</b><br>construction | T - Verbinder<br>T - connector              |
| <b>Werkstoff</b><br>material      | Polyamid 6, UL94 V0<br>polyamide 6, UL94 V0 |
| <b>Temperatur</b><br>temperature  | -40°C - +105°C                              |
| <b>Schutzart</b><br>protection    | IP66 / IP68 / IP69K                         |
| <b>gemäß</b><br>according to      | IEC EN 61386                                |

**T-Verteiler / T-connector**

| Art. Nr. IP66<br>art. no. IP66 | Art. Nr. IP68/69K<br>art. no. IP68/69K | NW<br>DN | L<br>mm | W<br>mm | E<br>mm | VPE Stk.<br>unit pcs. |
|--------------------------------|--|----------|---------|---------|---------|-----------------------|
| T6*101010                      | T8*101010                              | 10-10-10 | 69,8    | 44,9    | 21,0    | 20                    |
| T6*121212                      | T8*121212                              | 12-12-12 | 79,3    | 51,6    | 26,0    | 20                    |
| T6*171717                      | T8*171717                              | 17-17-17 | 86,7    | 28,3    | 32,0    | 20                    |
| T6*232323                      | T8*232323                              | 23-23-23 | 112,0   | 75,0    | 40,0    | 20                    |
| T6*292929                      | T8*292929                              | 29-29-29 | 121,0   | 83,2    | 48,0    | 10                    |
| T6*363636                      | T8*363636                              | 36-36-36 | 144,5   | 100,7   | 58,0    | 5                     |
| T6*484848                      | T8*484848                              | 48-48-48 | 169,5   | 118,7   | 70,0    | 5                     |

Die **Wellrohrverteiler-Anschlussarmatur Typ T** zur Aufteilung eingehender Leitungen ermöglicht die Zu- oder Wegführung von einzelnen Leitern an beliebiger Stelle am Wellrohr.

Geeignet für normale Anforderungen in technischen oder Elektroinstallations-Anwendungen, insbesondere für erhöhte Anforderungen in Industrie und Bahntechnik bei gleichzeitiger Abdichtung über das Wellrohr von bis zu IP69K.

**Distribution fitting type T** is conceived to divide conductor bundles into multiple conduit lines and allows inserting and exiting connection cables to any direction.

Suitable to standard requirements in industrial and electro technical installation applications as well as for increased requirements in heavy industry and railway applications also provide complementary liquid and tightness at the conduit itself until to IP69K.

