

Mainfix VS1202N / VSH



Ausführung
construction

Drehbare Verschraubung
swivelling fitting

Werkstoff
material

Polypropylene (PP)
UL94 V0
polypropylene (PP)
UL94 V0

Temperatur
temperature

-10°C - +110°C

Schutzart
protection

IP54

gemäß
according to

IEC EN 61386

VS1202N metrisch / metric

Art. Nr. grau art. no. grey RAL7001	Gewinde thread	Schlauch NW conduit DN	SW mm	GL mm	ID mm	VPE Stk. unit pcs.
VS1202N07M12	M12	7	17	7,5	5,5	50
VS1202N10M16	M16	10	20	8,5	8,8	50
VS1202N13M20	M20	13	24	9	11,1	50
VS1202N16M25	M25	16	30	10	14,8	50
VS1202N21M32	M32	21	36	11	19,4	25
VS1202N29M40	M40	29 / 30	46	12	27,9	25
VS1202N38M50	M50	38	55	13	35,6	25
VS1202N48M63	M63	48	65	13,5	45,9	10

VS1202N PG

Art. Nr. grau art. no. grey RAL7001	Gewinde thread	Schlauch NW conduit DN	SW mm	GL mm	ID mm	VPE Stk. unit pcs.
VS1202N07PG07	PG07	7	17	7,5	5,5	50
VS1202N10PG09	PG09	10	20	8,5	8,8	50
VS1202N13PG11	PG11	13	24	9	11,1	50
VS1202N15PG13	PG13,5	15	27	9,5	13,0	50
VS1202N16PG16	PG16	16	30	10	14,8	50
VS1202N21PG21	PG21	21	36	11	19,4	25
VS1202N29PG29	PG29	29 / 30	46	12	27,9	25
VS1202N38PG36	PG36	38	55	13	35,6	25
VS1202N44PG42	PG42	44	62	13	41,9	10
VS1202N48PG48	PG48	48	65	13,5	45,9	10

VS1202



VSH



Schlauchverschraubung mit drehbarem Aussen-
gewinde, für alle Kunststoffschläuche.

Swivel straight male fitting for plastic conduits.

VSH

Art. Nr. grau art. no. grey RAL7001	Schlauch NW conduit DN	ID mm	VPE Stk. unit pcs.
VSH1205N07	7	5,5	50
VSH1205N10	10	8,8	50
VSH1205N13	13	11,1	50
VSH1205N15	15	13,0	50
VSH1205N16	16	14,8	50
VSH1205N21	21	19,4	25
VSH1205N30	29 / 30	27,9	25
VSH1205N38	38	35,6	25
VSH1205N44	44	41,9	10
VSH1205N48	48	45,9	10

Starre Schlauchverschraubung mit integriertem
Halter, für alle Kunststoffschläuche.

Rigid straight fitting with integrated holder (clamp)
for plastic conduits.