



MAINFIX ECO

Mainfix ECO MEVG



Mainfix ECO

Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Polyamid 6 polyamide 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	UL94 V2



metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Gesamtlänge mm total length mm	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEVG07M12B	M12	07	35,0	12,0	50
MEVG10M12B	M12	10	37,0	12,0	50
MEVG10M16B	M16	10	37,0	12,0	50
MEVG12M16B	M16	12	39,5	12,0	50
MEVG12M16B	M20	12	39,5	13,0	50
MEVG14M20B	M20	14	42,0	13,0	50
MEVG17M20B	M20	17	45,0	13,0	50
MEVG17M25B	M25	17	45,0	13,0	50
MEVG22M25B	M25	22	46,5	13,5	25
MEVG23M25B	M25	23	37,0	13,0	25
MEVG23M32B	M32	23	37,0	13,0	25
MEVG29M32B	M32	29	44,0	15,0	25
MEVG29M40B	M40	29	44,0	15,0	25
MEVG36M40B	M40	36	52,0	15,0	10
MEVG36M50B	M50	36	52,0	15,0	10
MEVG48M50B	M50	48	64,0	16,0	5
MEVG48M63B	M63	48	64,0	16,0	5

Gerade Wellrohrverschraubung mit metrischem Kunststoff-Außengewinde.

Straight polyamide fitting with metric polyamide male thread.

PG

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Gesamtlänge mm total length mm	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEVG07P07B	PG07	07	35,0	12,0	50
MEVG10P09B	PG09	10	37,0	12,0	50
MEVG12P11B	PG11	12	39,5	12,0	50
MEVG14P13B	PG13	14	42,0	13,0	50
MEVG17P13B	PG13	17	42,0	13,0	50
MEVG17P16B	PG16	17	45,0	13,0	50
MEVG22P21B	PG21	22	47,0	13,0	50
MEVG23P21B	PG21	23	47,0	13,0	50
MEVG29P29B	PG29	29	51,0	15,0	50
MEVG36P36B	PG36	36	54,0	15,0	25
MEVG48P48B	PG48	48	55,0	16,0	25

Mainfix ECO MEVGZ



Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Polyamid 6 polyamide 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP66 / IP68
gemäß according to	UL94 V2

metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Kabel mm cable mm	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEVGZ07M12B	M12	07	3-6,5	8,0	50
MEVGZ10M16B	M16	10	4-8,0	8,0	50
MEVGZ12M16B	M16	12	5-10	9,0	50
MEVGZ14M20B	M20	14	6-12	9,0	50
MEVGZ17M20B	M20	17	8-14	10,0	50
MEVGZ23M25B	M25	23	13-18	11,0	25
MEVGZ29M32B	M32	29	18-25	11,0	10
MEVGZ36M40B	M40	36	22-32	13,0	10
MEVGZ48M50B	M50	48	30-38	15,0	5
MEVGZ48M63B	M63	48	37-44	15,0	5

Gerade Wellrohrverschraubung mit metrischem Kunststoff-Außengewinde und zentrischer Zugentlastung.

Straight polyamide fitting with metric polyamide male thread and strain relief.



Mainfix ECO MEVIG



Mainfix ECO

Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Polyamid 6 polyamide 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	UL94 V2



metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Gesamtlänge mm total length mm	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEVIG07M12B	M12	07	36,0	12,5	50
MEVIG10M12B	M12	10	38,5	13,0	50
MEVIG10M16B	M16	10	38,5	13,5	50
MEVIG12M16B	M16	12	41,0	13,5	50
MEVIG12M20B	M20	12	41,0	13,5	50
MEVIG14M20B	M20	14	43,0	13,5	50
MEVIG17M20B	M20	17	47,0	14,5	50
MEVIG17M25B	M25	17	47,0	14,5	50
MEVIG23M25B	M25	23	50,0	16,0	25
MEVIG23M32B	M32	23	50,0	16,0	25
MEVIG29M32B	M32	29	56,0	17,0	25
MEVIG29M40B	M40	29	56,0	17,5	25
MEVIG36M40B	M40	36	65,0	26,0	10
MEVIG36M50B	M50	36	65,0	26,0	10
MEVIG48M50B	M50	48	68,5	28,5	5
MEVIG48M63B	M63	48	68,5	28,5	5

Gerade Wellrohrverschraubung mit metrischem Kunststoff-Innengewinde.

Straight polyamide fitting with metric polyamide female thread.

Mainfix ECO MEVW



Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Polyamid 6 polyamide 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	UL94 V2



metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Gesamtlänge mm total length mm	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEVW07M12B	M12	07	-	11,5	50
MEVW10M12B	M12	10	-	11,5	50
MEVW10M16B	M16	10	-	11,5	50
MEVW12M16B	M16	12	-	12,0	50
MEVW12M20B	M20	12	-	12,0	50
MEVW14M20B	M20	14	-	13,0	50
MEVW17M20B	M20	17	-	13,0	50
MEVW17M25B	M25	17	-	13,0	50
MEVW23M25B	M25	23	-	13,0	25
MEVW23M32B	M32	23	-	13,0	25
MEVW29M32B	M32	29	-	15,0	25
MEVW29M40B	M40	29	-	15,0	25
MEVW36M40B	M40	36	-	15,0	10
MEVW36M50B	M50	36	-	15,0	10
MEVW48M50B	M50	48	-	16,0	5
MEVW48M63B	M63	48	-	16,0	5

90° Wellrohrverschraubung mit metrischem Kunststoff-Außengewinde.

90° polyamide fitting with metric polyamide male thread.

Mainfix ECO MEVB



Mainfix ECO

Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Polyamid 6 polyamide 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	UL94 V2

metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Gesamtlänge mm total length mm	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEVB07M12B	M12	07	35,0	12,0	50
MEVB10M16B	M16	10	37,0	12,0	50
MEVB12M16B	M16	12	39,5	12,0	50
MEVB14M20B	M20	14	42,0	13,0	50
MEVB17M20B	M20	17	45,0	13,0	50
MEVB17M25B	M25	17	45,0	13,0	50
MEVB23M25B	M25	23	37,0	13,0	25
MEVB23M32B	M32	23	37,0	13,0	25
MEVB29M32B	M32	29	44,0	15,0	25
MEVB29M40B	M40	29	44,0	15,0	25
MEVB36M40B	M40	36	52,0	15,0	10
MEVB36M50B	M50	36	52,0	15,0	10
MEVB48M50B	M50	48	64,0	16,0	5
MEVB48M63B	M63	48	64,0	16,0	5



90° Bogen-Wellrohrverschraubung mit metrischem Kunststoff-Außengewinde. mit metrischem Kunststoff-Außengewinde. 90° elbow polyamide fitting with metric polyamide male thread.

Mainfix ECO MEV



Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Nitril Gummi nitrile rubber
Temperatur temperature	-40°C - +120°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	-

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW 1 tube DN 1	Wellrohr NW 1 tube DN 1	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEV07B	-	07	07	33,5	20
MEV10B	-	10	10	36,5	10
MEV12B	-	12	12	44,5	10
MEV14B	-	14	14	48,0	10
MEV17B	-	17	17	46,0	10
MEV23B	-	23	23	46,0	10
MEV2329B	-	23	29	48,0	10
MEV29B	-	29	29	48,0	10
MEV36B	-	36	36	60,0	10
MEV48B	-	48	48	70,0	5

Wellrohrverbinder

corrugated tube connector



Mainfix ECO MEY



Mainfix ECO

Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Nitril Gummi nitrile rubber
Temperatur temperature	-40°C - +120°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	-

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW 1 tube DN 1	Wellrohr NW 2x tube DN 2x	Gewindelänge mm thread length mm	VPE Stk. unit pcs.
MEY070707B	-	07	07	-	25
MEY171212B	-	17	12	-	25
MEY231212B	-	23	12	-	20
MEY141414B	-	14	14	-	20
MEY171717B	-	17	17	-	10
MEY231717B	-	23	17	-	10
MEY292323B	-	29	23	-	5
MEY362929B	-	36	29	-	5
MEY483636B	-	48	36	-	5

Y-Verteiler

Y-connector



Mainfix ECO MET



Ausführung construction	Wellrohrverschraubungen corrugated tube fittings
Werkstoff material	Nitril Gummi nitrile rubber
Temperatur temperature	-40°C - +120°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	-

metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW 1 tube DN 1	Wellrohr NW 2 tube DN 2	Wellrohr 3 tube DN 3	VPE Stk. unit pcs.
MET070707B	-	07	07	07	50
MET101010B	-	10	10	10	50
MET121212B	-	12	12	12	5
MET141414B	-	14	14	14	50
MET171717B	-	17	17	17	50
MET231717B	-	23	17	17	50
MET122323B	-	12	23	23	50
MET292323B	-	29	23	23	25
MET292929B	-	29	29	29	25
MET363636B	-	36	36	36	10

T-Verteiler

T-connector



Mainfix ECO GZ



Mainfix ECO

Ausführung construction	Zugentlastung-Endtülle strain relief end cab
Werkstoff material	TPE tpe
Temperatur temperature	-40°C - +120°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	-

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Kabel mm cable mm	Gesamtlänge mm total length mm	VPE Stk. unit pcs.
GZ10B08	-	07	2-8	29,0	50
GZ13B10	-	10	3-10	29,5	50
GZ16B12	-	12	4-12	36,5	50
GZ18B13	-	14	4-13	37,5	50
GZ21B16	-	17	6-16	37,5	50
GZ28B23	-	23	6-23	40,2	20
GZ34B29	-	29	7-29	44,2	20
GZ42B37	-	36	10-37	46,0	10
GZ54B47	-	48	10-47	52,0	2



Mainfix ECO CTS



Ausführung construction	PA Endtülle PA end cab
Werkstoff material	Polyamid 6 polyamide 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	-

Art. Nr. schwarz art. no. black	Gewinde thread	Wellrohr NW tube DN	Gesamtlänge mm total length mm	VPE Stk. unit pcs.
CTSB07	-	07	-	25
CTSB10	-	10	-	25
CTSB12	-	12	-	20
CTSB14	-	14	-	20
CTSB17	-	17	-	10
CTSB23	-	23	-	10
CTSB29	-	29	-	5
CTSB36	-	36	-	5
CTSB48	-	48	-	5




Mainfix ECO SC



Ausführung construction	Wellrohrhalter clamp
Werkstoff material	Polyamid 6 polyamid 6
Temperatur temperature	-40°C - +120°C
kurzzeitig short term	+150°C
Schutzart protection	IP66
gemäß according to	-

Art. Nr. schwarz art. no. black	Wellrohr NW tube DN	VPE Stk. unit pcs.
SCB07	07	100
SCB10	10	100
SCB12	12	100
SCB17	17	100
SCB23	23	50
SCB29	29	50
SCB36	36	50
SCB48	48	50

Mainfix ECO




Mainfix ECO WSH



Ausführung construction	Wellrohrhalter clamp
Werkstoff material	Polyamid 6 polyamid 6
Temperatur temperature	-40°C - +115°C
kurzzeitig short term	+150°C
Schutzart protection	IP65
gemäß according to	-

Art. Nr. Deckel schwarz art. no. cover black	Art. Nr. Halter schwarz art. no. clamp black	Art. Nr. Bodenplatte schwarz art. no. plate black	Wellrohr NW tube DN	VPE Stk. unit pcs.
WSHD07B	WSH07B	WSHF07B	07	100
WSHD10B	WSH10B	WSHF10B	10	100
WSHD12B	WSH12B	WSHF12B	12	100
WSHD17B	WSH17B	WSHF17B	17	100
WSHD23B	WSH23B	WSHF23B	23	50
WSHD29B	WSH29B	WSHF29B	29	50
WSHD36B	WSH36B	WSHF36B	36	50
WSHD48B	WSH48B	WSHF48B	48	50

Art. Nr. kompletter Halter schwarz art. no. complete clamp black	Wellrohr NW tube DN	VPE Stk. unit pcs.
WSH07BK	07	100
WSH10BK	10	100
WSH12BK	12	100
WSH17BK	17	100
WSH23BK	23	50
WSH29BK	29	50
WSH36BK	36	50
WSH48BK	48	50



LAGRA
SYSTEMTECHNIK

 **MAINCOR** brand

Lagra Systemtechnik GmbH
Im Schiff 14
D-68789

Tel.: +49 (0) 6227 / 35890-100
Fax: +49 (0) 6227 / 35890-200

www.lagra.de